

Standard Lockers



Sizes & Compartments Available

Sizes:

1800Hx300Wx300Dmm

1800Hx300Wx450Dmm

1800Hx380Wx380Dmm

1800Hx450Wx450Dmm

Door Compartment Options:

1 Compartment

2 Compartments

3 Compartments

4 Compartments

5 Compartments

6 Compartments

Internal Compartment Sizes:

1800Hx300Wx300Dmm

1 Compartment - 1698Hx245Wx275Dmm

2 Compartments - 830Hx245Wx275Dmm

3 Compartments - 548Hx245Wx275Dmm

4 Compartments - 408Hx245Wx275Dmm

5 Compartments - 318Hx245Wx275Dmm

6 Compartments - 260Hx245Wx275Dmm

1800Hx300Wx450Dmm

1 Compartment - 1698Hx245Wx430Dmm

2 Compartments - 830Hx245Wx430Dmm

3 Compartment - 548Hx245Wx430Dmm

4 Compartments - 408Hx245Wx430Dmm

5 Compartments - 318Hx245Wx430Dmm

6 Compartments - 260Hx245Wx430mm



Standard Lockers



1800Hx380Wx380Dmm

- 1 Compartment - 1698Hx330Wx360Dmm
- 2 Compartments - 830Hx330Wx360Dmm
- 3 Compartments - 546Hx330Wx360Dmm
- 4 Compartments - 408Hx330Wx360Dmm
- 5 Compartments - 318Hx330Wx360Dmm
- 6 Compartments - 260Hx330Wx360Dmm

1800Hx450Wx450Dmm

- 1 Compartment - 1698Hx395Wx430Dmm
- 2 Compartments - 830Hx395Wx430Dmm
- 3 Compartments - 546Hx395Wx430Dmm
- 4 Compartments - 408Hx395Wx430Dmm
- 5 Compartments - 315Hx395Wx430Dmm
- 6 Compartments - 260Hx395Wx430Dmm



Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180 deg, including our germ guard anti-bacterial compound.

The carcass is powder-coated - Light Grey RAL 7035.

Doors are powder-coated with a choice of Dark Grey RAL 7024, Red RAL 3003, Green RAL 6024, Light Grey RAL 7035, Light Blue RAL 5012, Dark Blue RAL 5017 & Yellow RAL 1018.



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).

Standard Lockers



Locker Construction

General Construction:

- 0.7mm mild steel, pop riveted carcass construction.
- Rust-resisting galvanised shelves.
- Delivered as a fully assembled unit.
- Pre-drilled carcass for nesting lockers together to complete a run/bank.
- Fitted with standard master cam locks with 2,000 differs.
- Single compartment locker fitted with top shelf and coat hook.
- Two-tier lockers fitted with coat hook in each compartment.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.

Locker Door Construction:

- A door stiffener is spot welded vertically in the centre of the door (except for 6 door units), the door is attached by pop rivets to the right-hand side of the carcass with two 38mm butt hinges and fitted with 10 disc key operated cam lock. Alternatively, swivel latch locks (*to accept padlocks supplied by others*) can be specified.



Replacement Locks & Spare Keys

Replacement locks and keys are available from QMP.
Replacement keys are available from CS Storage Ltd.
www.csstorage.co.uk - sales@csstorage.co.uk.



Delivery

All sizes and compartment options are manufactured-to-order item and will be on an extended lead-time.



Our live chat satisfaction rating,
based on user feedback